

Poroelastic measurements resulting in complete data sets for granular and other anisotropic porous media

James G. Berryman

ABSTRACT

Poroelastic analysis usually progresses from assumed knowledge of dry or drained porous media to the predicted behavior of fluid-saturated and undrained porous media. Unfortunately, the experimental situation is often incompatible with these assumptions, especially when field data (from hydrological or oil/gas reservoirs) are involved. The present work considers several different experimental scenarios typified by one in which a set of undrained poroelastic (stiffness) constants has been measured using either ultrasound or seismic wave analysis, while some or all of the dry or drained constants are normally unknown. Drained constants for such a poroelastic system can be deduced for isotropic systems from available data if a complete set of undrained compliance data for the principal stresses is available, together with a few other commonly measured quantities such as porosity, fluid bulk modulus, and grain bulk modulus. Similar results are also developed here for anisotropic systems having up to orthotropic symmetry if the system is granular (*i.e.*, composed of solid grains assembled into a solid matrix, either by a cementation process or by applied stress) and the grains are known to be elastically homogeneous. Finally, the analysis is also fully developed for anisotropic systems with nonhomogeneous (more than one mineral type), but still isotropic, grains — as well as for uniform collections of anisotropic grains as long as their axes of symmetry are either perfectly aligned or perfectly random.

INTRODUCTION

Poroelastic analysis (Gassmann, 1951; Biot and Willis, 1957; Brown and Korringa, 1975; Rice and Cleary, 1976; Thigpen and Berryman, 1985; Cheng, 1997; Wang, 2000) usually progresses from assumed knowledge of dry or drained porous media to the predicted behavior of fluid-saturated and undrained porous media. When field data (say from oil, gas, or hydrological reservoirs) are involved, the experimental situation is generally and unfortunately incompatible with these assumptions.

For this reason, I want to consider several different experimental scenarios typified by one in which a set of undrained constants has been measured using either ultrasound (in the laboratory) or seismic wave analysis (for field data), while some or all of the dry or drained constants are usually unmeasured and therefore unknown.

Drained constants for such a poroelastic system can be deduced from available data if a complete set of undrained compliance data (as could be calculated by inverting the stiffness data, which are almost directly obtained, within a factor of the density, from wave speed measurements) is available, together with a few other commonly measured quantities such as porosity, fluid bulk modulus, and grain bulk modulus for isotropic systems. Similar results are developed here for anisotropic systems having up to orthotropic symmetry if the system is granular (*i.e.*, composed of solid grains assembled into solid either by a cementation process or by applied stress) and the grains are known to be elastically homogeneous.

In the later sections, the analysis is also fully developed for anisotropic systems with inhomogeneous (meaning more than one mineral type is present), but still isotropic, grains. Also studied is the case for uniform collections of the same types of anisotropic grains, as long as the grain symmetry axes are either perfectly aligned or perfectly random. I show how many poroelastic data are needed in order to consider the data sets complete, and which types of data are in some sense redundant. Some combinations can be used to replace other data types that remain missing when lab experimental and/or field limitations prevent direct measurements of all the poroelastic coefficients.

ISOTROPIC POROELASTICITY

Homogeneous grains

The famous equation for undrained bulk modulus named for Gassmann (1951) can be written in the form

$$K^u = K^d + \alpha^2 / [(\alpha - \phi) / K^g + \phi / K_f] \quad (1)$$

for isotropic systems, where $\alpha \equiv 1 - K^d / K^g$ is the Biot-Willis coefficient or effective stress (Biot and Willis, 1957) coefficient, K^g is the solid modulus of the grains (assumed homogeneous), K^d is the drained modulus of the porous medium, K_f is the pore fluid modulus, and ϕ is the porosity. The formula becomes more complicated if the solids constituting the porous medium are heterogeneous. But we will delay discussion of this point to the next subsection and for now assume that the solids are truly homogeneous. For notational convenience, I next introduce a modulus for a fluid suspension having the same solid and fluid components as well as the same porosity, but having drained modulus $K^d \equiv 0$. Then I find that the effective modulus is given by

$$K_{susp} = \left[\frac{1 - \phi}{K^g} + \frac{\phi}{K_f} \right]^{-1}. \quad (2)$$

In fact this result follows directly from Gassmann's formula (1) by setting $K^d = 0$ everywhere, since then $K^u = K_{susp}$. But of course this result is also well-known in mechanics and acoustics (Wood, 1955) for these types of fluid-solid suspensions.

Deducing drained moduli from undrained: Isotropic system with homogeneous grains

Rewriting Gassmann's formula in these terms, I first find that

$$K^u = K^d + \frac{(1 - K^d/K^g)^2}{1/K_{susp} - K^d/(K^g)^2}. \quad (3)$$

Note that all explicit porosity (ϕ) dependence is now imbedded in the modulus K_{susp} . Now if I simply multiply through by the denominator on the right hand side, then I find

$$K^u \left(\frac{1}{K_{susp}} - \frac{K^d}{(K^g)^2} \right) = 1 - 2\frac{K^d}{K^g} + \frac{K^d}{K_{susp}}. \quad (4)$$

Also notice that two terms of the form $(K^d/K^g)^2$ have cancelled from this expression. Once these convenient cancellations have occurred, K^d appears only linearly in the resulting expression. The equation can therefore be solved immediately for drained modulus K^d in terms of the undrained modulus K^u and the other factors that are also assumed to be known (and in fact these other factors are usually easier to measure than either K^u or K^d). Finally, I obtain:

$$K^d = \left(\frac{K^u}{K_{susp}} - 1 \right) [1/K_{susp} - 2/K^g + K^u/(K^g)^2]^{-1}. \quad (5)$$

This result shows that the drained modulus can be deduced from measurements of the undrained modulus, together with knowledge of ϕ , K_f , and K^g . Note that this result was first derived by Zhu and McMechan (1990), but apparently published only in an SEG conference proceedings.

Heterogeneous grains

When the grains in a granular packing are no longer composed of elastically homogeneous and isotropic materials, or if they are homogeneous but anisotropic while nevertheless being distributed in a randomly oriented way in space, then — as has been pointed out previously in Brown and Korringa (1975), Rice and Cleary (1976), and the work of others [*e.g.*, Wang (2000)] — I need to introduce a more general notation to deal with these circumstances.

Recall that the Reuss (1929) average of the grain bulk moduli for a heterogeneous medium with a distribution of grain types is given by:

$$\frac{1}{K_R^g} \equiv \sum_{m=1, \dots, n} \frac{v_m}{K_m}, \quad (6)$$

where v_m is the volume fraction (out of all the solid material present, so that $\sum_m v_m = 1$) of the m -th isotropic grain having bulk modulus K_m . This average should be

distinguished from that of the Voigt (1928) average

$$K_V^g \equiv \sum_{m=1, \dots, n} v_m K_m, \quad (7)$$

which is known (Hill, 1952) to satisfy $K_V^g \geq K_R^g$. Furthermore, these two measures are also known (Reuss, 1929; Voigt, 1928; Hill, 1952) to satisfy $K_V^g \geq K_g^* \geq K_R^g$, where K_g^* is the effective bulk modulus of an isotropic elastic composite consisting only of the minerals $m = 1, \dots, n$ in the same volume proportions given by the v_m values. However, this fact actually is not pertinent here, as the only averages of this type that play a direct role in the poroelastic equations are always those of the Reuss-type, as will be shown in the further developments.

To clarify later usage of the same notation K_R^g , I emphasize here that when (or if) the grains in our assemblage are all anisotropic — but nevertheless of the same type and oriented randomly in space — then the pertinent average is again the Reuss average. But in this case the average is determined by the equation

$$\frac{1}{K_R^g} = \sum_{i,j=1,2,3} s_{ij}^g, \quad (8)$$

where the s_{ij}^g for $i, j = 1, 2, 3$ are the principal components of the compliance matrix for the anisotropic grain material itself. It is easy to see that this must be the case by referring back to the equations above, specifically those requiring the suspension result K_{susp} . The formula as quoted in (2) was only written for the case of homogeneous grains. But if we generalize this formula slightly as:

$$K_{susp} \equiv \left[\frac{1 - \phi}{K_R^g} + \frac{\phi}{K_f} \right]^{-1}, \quad (9)$$

then we see that it holds equally true: (a) for homogeneous isotropic grains (when $K_R^g \equiv K^g$), (b) for heterogeneous volumes of isotropic grains [when K_R^g is given by (6)], or (c) for anisotropic grains when they are randomly oriented in the fluid [and then K_R^g is given by (8)]. In all these cases, I do assume that this mixture of grains and fluid is close to being a true suspension, by which we mean that individual grains are acted on similarly by changes in fluid pressure.

If the clumpings are loose enough, then the fluid can act equally on all the individual grains, and the result in (9) holds true regardless of the heterogeneity. However, if this is not the case, then there must be elastically distinct clumpings of grains forming solid composites locally — so the individual grains are no longer uniformly surrounded by the pore fluid. Then, each grain's fluid environment is different, due to welded contacts with other contiguous grains. I am assuming for the present purposes that such effects are negligible in the types of comparatively homogeneous porous media (on the meso- and macroscales, but not necessarily on the microscale) being studied here. In fact, some types of more heterogeneous systems can be treated, and some of these have already been studied (Berryman and Milton, 1991; Berryman and Pride,

2002) when the porous system is composed of just two distinct types of grain clumpings; however, I will not be discussing such double-porosity and/or multi-porosity effects in the present paper.

Heterogeneous pores

Another important type of heterogeneity that can occur in practice involves heterogeneity of the pore space. One obvious issue is whether the pores are all connected to each other, or whether there may be two (or more) distinct, but intertwining, pore systems. One well-known example of this situation is the double-porosity concept (Berryman and Pride, 2002; Gurevich et al., 2009; Barenblatt and Zheltov, 1960), in which one type of pore has high volume but low permeability, while the other has low volume (imagine a system of very flat cracks or fractures) and high permeability. I can also consider that some pores might be interior to some grains and not connected to any other pores (and might therefore also be empty of pore fluid), while other subsets of the grains have no inherent porosity of this type, and so are truly solid grains.

I will not try to deal with all these cases simultaneously, as even enumerating all the possibilities quickly becomes burdensome. I will limit myself instead to one of the more typical scenarios, considered for example by Brown and Korrington (1975) and by Rice and Cleary (1976) — and also see the recent related work of Gurevich et al. (2009).

Heterogeneity of the pore space is most important when considering flow of fluid into and out of the boundaries of a porous sample. Then, the concept of increment of fluid content ζ comes into play, and special care is required. A straightforward definition of this dimensionless parameter (just as the strains e_{11} , e_{22} , \dots , e_{13} are all dimensionless) is given by:

$$\zeta \equiv \frac{\delta(\phi V) - \delta V_f}{V} \simeq \phi \left(\frac{\delta V_\phi}{V_\phi} - \frac{\delta V_f}{V_f} \right), \quad (10)$$

where V is the overall volume of the initially fully fluid-saturated porous material at the first instant of consideration, $V_\phi = \phi V$ is the pore volume, with ϕ being the fluid-saturated porosity of the volume, and V_f is the volume occupied by the pore-fluid, making $V_f = \phi V$ at the start. The δ 's indicate small changes in the quantities following. For “drained” systems, there must be a reservoir of the same fluid just outside the volume V that can either supply more fluid or absorb any excreted fluid as needed during the nonstationary phase of the poroelastic process; the amount of pore fluid can therefore either increase or decrease from the initial amount of pore fluid, and at the same time the pore volume can also be changing, but not necessarily at exactly the same rate as the pore fluid itself. The one exception to these statements is when the surface pores of the total volume V are sealed, in which case the system is “undrained” and $\zeta \equiv 0$, identically. In these circumstances, it is still possible that

V_f and $V_\phi = \phi V$ are both changing, but because of the imposed undrained boundary conditions, they are necessarily changing at the same rate. The result is that, for an isotropic system, I have:

$$\zeta = \phi \left[\frac{\delta\sigma_c}{K_p} + \delta p_f \left(\frac{1}{K_p} - \frac{1}{K_R^\phi} + \frac{1}{K_f} \right) \right], \quad (11)$$

and where the various moduli in (11) are defined by the following relations [see Brown and Korringa (1975)]:

$$-\frac{\delta V_f}{V_f} = \frac{\delta p_f}{K_f}, \quad (12)$$

$$-\frac{\delta V}{V} = \frac{\delta p_d}{K_R^d} + \frac{\delta p_f}{K_R^g}, \quad (13)$$

and

$$-\frac{\delta V_\phi}{V_\phi} = \frac{\delta p_d}{K_p} + \frac{\delta p_f}{K_R^\phi}. \quad (14)$$

The changes in fluid pressure and differential pressure are respectively δp_f and $\delta p_d \equiv \delta p_c - \delta p_f$, where $\delta p_c = -\delta\sigma_c$ is the uniform confining pressure, if the external confining pressure is uniform. If not, then this quantity is replaced in the definition of δp_c by $-\delta\sigma_m$, which is the change in the mean confining pressure and where $\sigma_m \equiv (\sigma_{11} + \sigma_{22} + \sigma_{33})/3$ is the definition of the mean principal stress. Clearly, if the confining principal stress is uniform ($\sigma_{11} = \sigma_{22} = \sigma_{33}$), then the mean stress equals this uniform confining stress. If not, then there can be additional shearing effects that need to be taken into account, but these do not play any role in the changes of fluid content since this quantity is effectively a measure only of the total number of fluid particles contained in the pertinent pore volume.

It can also be shown using poroelastic reciprocity (and I will show this later as it very clearly develops in the following anisotropic analysis) that

$$\frac{\phi}{K_p} = \frac{\alpha_R}{K_R^d} = \frac{1}{K_R^d} - \frac{1}{K_R^g}. \quad (15)$$

So generalizing Gassmann's formula for undrained modulus gives:

$$\frac{1}{K_R^u} = \frac{1 - \alpha_R B}{K_R^d}, \quad (16)$$

where $\alpha_R = 1 - K_R^d/K_R^g$ and

$$B = \left(\frac{1}{K_R^d} - \frac{1}{K_R^g} \right) \left[\left(\frac{1}{K_R^d} - \frac{1}{K_R^g} \right) + \phi \left(\frac{1}{K_f} - \frac{1}{K_R^\phi} \right) \right]^{-1} \quad (17)$$

is the second coefficient of Skempton (1954). Combining these terms, I find that the most general form of the equation for the undrained bulk modulus in the isotropic case is:

$$\frac{1}{K_R^u} = \frac{1}{K_R^d} - \left(\frac{1}{K_R^d} - \frac{1}{K_R^g} \right)^2 \left[\left(\frac{1}{K_R^d} - \frac{1}{K_R^g} \right) + \phi \left(\frac{1}{K_f} - \frac{1}{K_R^\phi} \right) \right]^{-1}, \quad (18)$$

or, alternatively,

$$\frac{1}{K_R^u} = \frac{1}{K_R^d} - \frac{(\alpha_R/K_R^d)^2}{\alpha_R/K_R^d + \phi \left(\frac{1}{K_f} - \frac{1}{K_R^\phi} \right)}, \quad (19)$$

which is the isotropic result of Brown and Korrington (1975), and should also be compared directly to (1). So, if the pore modulus and grain modulus are equal with $K_R^\phi = K_R^g$, then (19) reduces exactly to (1). Although this result is the same as that of Brown and Korrington (1975), I nevertheless write it differently to emphasize different features.

Deducing drained constants from undrained: Heterogeneous grains and pores

I was able to deduce K_R^d from our knowledge of K_R^u , K_R^g , K_f , and ϕ in subsection 2.2. But even though I am still assuming the system is isotropic, I have now introduced some additional degrees of freedom by permitting the grains and pores to be heterogeneous. It is clear that I cannot deduce K_R^d if I just have the same amount of information as before. In particular, it does seem fairly straightforward to measure K_R^g , as I have already described its meaning in the earlier discussion and even given formulas for it — if I have information about the constituents and their volume fractions, or alternatively about the principal components of elastic compliance and/or stiffness matrices. But I have another variable now, which is the pore modulus K_R^ϕ , and this bulk modulus is not so easy either to model or to measure directly (Lockner and Stanchits, 2002). However, by adding one more piece of information — namely the second Skempton coefficient $B = p_f/p_c$, which is a fact that should typically be known in poroelastic systems — then it turns out that I can solve for both K_R^d and K_R^ϕ . Again, I assume that K_R^g and K_R^u are known. But now I also assume that B is also known experimentally. Working through the algebra, I find that

$$K_R^d = \frac{1 - B}{1/K_R^u - B/K_R^g} \quad (20)$$

[which is a rearrangement of $K_R^u = K_R^d/(1 - \alpha_R B)$], and similarly that

$$\frac{1}{K_R^\phi} = \frac{1}{K_f} - \left(\frac{1 - B}{\phi B} \right) \left(\frac{1}{K_R^d} - \frac{1}{K_R^g} \right) = \frac{1}{K_f} - \left(\frac{1}{\phi B} \right) \left(\frac{1}{K_R^u} - \frac{1}{K_R^g} \right). \quad (21)$$

In (21), I used the previous result (20) for K_R^d to simplify the final formula.

These forms are very useful for many applications in poroelasticity, but so far they apply only to the fully isotropic case. I show next that a very similar set of formulas applies to the anisotropic cases under consideration. I am able to attain greater clarity at this point by switching to the more general anisotropic problem, where it can be seen more easily how poroelastic reciprocity comes directly into play.

ANISOTROPIC POROELASTICITY

If the overall porous medium is anisotropic due either to some preferential alignment of the constituent particles or to externally imposed stress (such as a gravity field and weight of overburden, for example), I consider the orthorhombic anisotropic version of the poroelastic equations:

$$\begin{pmatrix} e_{11} \\ e_{22} \\ e_{33} \\ -\zeta \end{pmatrix} = \begin{pmatrix} s_{11} & s_{12} & s_{13} & -\beta_1 \\ s_{12} & s_{22} & s_{23} & -\beta_2 \\ s_{13} & s_{23} & s_{33} & -\beta_3 \\ -\beta_1 & -\beta_2 & -\beta_3 & \gamma \end{pmatrix} \begin{pmatrix} \sigma_{11} \\ \sigma_{22} \\ \sigma_{33} \\ -p_f \end{pmatrix}. \quad (22)$$

From here on throughout the paper, I will drop the δ 's from the stresses and strains, as this extra notation is truly redundant when they are all being treated as small (and therefore resulting in linear effects), as I do here.

The e_{ii} are strains in the $i = 1, 2, 3$ directions. The σ_{ii} are the corresponding stresses. The fluid pressure is p_f . The increment of fluid content is ζ . The drained compliances are $s_{ij} = s_{ij}^d$. Undrained compliances (not yet shown) are symbolized by s_{ij}^u . Coefficients $\beta_i = s_{i1} + s_{i2} + s_{i3} - 1/3K_R^g$, where K_R^g is again the Reuss average modulus of the grains. The drained Reuss average bulk modulus is defined by

$$\frac{1}{K_R^d} = \sum_{ij=1,2,3} s_{ij}^d. \quad (23)$$

For the Reuss average undrained bulk modulus K_R^u , I have drained compliances replaced by undrained compliances. A similar definition of K_R^g , with drained compliances replaced by grain compliances has already been introduced earlier in the discussion. The alternative Voigt (1928) average [also see Hill (1952)] of the stiffnesses will play no role in the present work. And, finally, $\gamma = \sum_{i=1-3} \beta_i / BK_R^d$, where B is the second Skempton (1954) coefficient, which will be defined carefully again later in our discussion.

The shear terms due to twisting motions (*i.e.*, strains e_{23} , e_{31} , e_{12} and stresses σ_{23} , σ_{31} , σ_{12}) are excluded from this discussion since they typically do not couple to the modes of interest for anisotropic systems having orthotropic symmetry, or any more symmetric system such as transversely isotropic or isotropic. I have also assumed that the true axes of symmetry are known, and make use of them in my formulation of the problem. Note that the s_{ij} 's are the elements of the compliance matrix \mathbf{S} and are all independent of the fluid, and therefore would be the same if the medium were treated as elastic (*i.e.*, by ignoring the fluid pressure, or assuming that the fluid saturant is air). In keeping with the earlier discussions, I typically call these compliances the drained compliances and the corresponding matrix the drained compliance matrix \mathbf{S}^d , since the fluids do not contribute to the stored mechanical energy if they are free to drain into a surrounding reservoir containing the same type of fluid. In contrast, the undrained compliance matrix \mathbf{S}^u presupposes that the fluid is trapped (unable to drain from the system into an adjacent reservoir) and therefore contributes in a

significant and measureable way to the compliance and stiffness ($\mathbf{C}^u = [\mathbf{S}^u]^{-1}$), and also therefore to the stored mechanical energy of the undrained system.

Although the significance of the formula is somewhat different now, I find again that

$$\beta_1 + \beta_2 + \beta_3 = \frac{1}{K_R^d} - \frac{1}{K_R^g} = \frac{\alpha_R}{K_R^d}, \quad (24)$$

if I also define (as I did for the isotropic case) a Reuss effective stress coefficient:

$$\alpha_R \equiv 1 - K_R^d/K_R^g. \quad (25)$$

Furthermore, I have

$$\gamma = \frac{\beta_1 + \beta_2 + \beta_3}{B} = \frac{\alpha_R}{K_R^d} + \phi \left(\frac{1}{K_f} - \frac{1}{K_R^\phi} \right), \quad (26)$$

since I have the rigorous result in this notation (Berryman, 1997) that Skempton's B coefficient is given by

$$B \equiv \frac{1 - K_R^d/K_R^u}{1 - K_R^d/K_R^g} = \frac{\alpha_R/K_R^d}{\alpha_R/K_R^d + \phi(1/K_f - 1/K_R^\phi)}. \quad (27)$$

Note that both (26) and (27) contain dependence on the pore bulk modulus K_R^ϕ that comes into play when the pores are heterogeneous, regardless of whether the system is isotropic or anisotropic. I want to emphasize that all these formulas are rigorous statements based on the earlier anisotropic analysis. The appearance of K_R^d and α_R is not an approximation, but merely a useful choice of notation made here because it will make clear the similarity between the rigorous anisotropic formulas and the isotropic ones.

The β_i coefficients

I will now provide several results for the β_i coefficients, and then follow the results with a general proof of their correctness.

In many important and useful cases, the coefficients β_i are determined by

$$\beta_i = s_{i1}^d + s_{i2}^d + s_{i3}^d - \frac{1}{3K_R^g}. \quad (28)$$

Again, K_R^g is the Reuss average of the grain modulus, since the local grain modulus is not necessarily assumed uniform here as mentioned previously. Equation (28) holds true for homogeneous grains, such that $K_R^g = K^g$. It also holds true for the case when K_R^g is determined instead by (6). However, when the grains themselves are anisotropic, I need to allow again for this possibility, and this can be accomplished by defining three directional grain bulk moduli determined by:

$$\frac{1}{3K_i^g} \equiv s_{i1}^g + s_{i2}^g + s_{i3}^g = s_{1i}^g + s_{2i}^g + s_{3i}^g, \quad (29)$$

for $i = 1, 2, 3$. The second equality follows because the compliance matrix is always symmetric. I call these quantities in (29) the partial grain-compliance sums, and the \overline{K}_i^g are the directional grain bulk moduli. Then, the formula for (28) is replaced by

$$\beta_i = s_{i1}^d + s_{i2}^d + s_{i3}^d - \frac{1}{3\overline{K}_i^g}. \quad (30)$$

Note that the factors of three have been correctly accounted for because

$$\sum_{i=1,2,3} \frac{1}{3\overline{K}_i^g} = \frac{1}{K_R^g}, \quad (31)$$

in agreement with (8). If the three contributions represented by (29) for $i = 1, 2, 3$ happen to be equal, then each equals one-third of the sum (31).

The preceding results are for perfectly aligned grains. If the grains are instead perfectly randomly oriented, then it is clear that the formulas in (28) hold as before, but now K_R^g is determined instead by (8).

All of these statements about the β_i are easily proven by considering the case when $\sigma_{11} = \sigma_{22} = \sigma_{33} = -p_c = -p_f$. In this situation, from (22), I have:

$$-e_{ii} = (s_{i1}^d + s_{i2}^d + s_{i3}^d) p_c + \beta_i (-p_f) = (s_{i1}^g + s_{i2}^g + s_{i3}^g) p_f \equiv \frac{p_f}{3\overline{K}_i^g}, \quad (32)$$

in the most general of the three cases discussed, and holding true for each value of $i = 1, 2, 3$. This is a statement about the strain e_{ii} that would be observed in this situation, as it must be the same if these anisotropic (or inhomogeneous) grains were immersed in the fluid, while measurements were taken of the strains observed in each of the three directions $i = 1, 2, 3$, during variations of the fluid pressure p_f . Consider this proof to be a thought experiment for determining the coefficients, in the same spirit as those proposed originally by Biot and Willis [see Biot and Willis (1957); Stoll (1974)] for the isotropic and homogeneous case.

Coefficient γ

The relationship of coefficient γ to the other coefficients is easily established because I have already discussed the main issue, which involves determining the role of the various other constants contained in the Skempton (1954) coefficient B . I have quoted this result in (17).

Again, from (22), I find that

$$-\zeta = 0 = -(\beta_1 + \beta_2 + \beta_3) \sigma_c - \gamma p_f, \quad (33)$$

for undrained boundary conditions. Thus, I again have

$$\frac{p_f}{p_c} \equiv B = \frac{\beta_1 + \beta_2 + \beta_3}{\gamma}, \quad (34)$$

where $p_c = -\sigma_c$ is the confining pressure. Thus, the scalar coefficient γ is determined immediately and given by

$$\gamma = \frac{\beta_1 + \beta_2 + \beta_3}{B} = \frac{\alpha_R/K_R^d}{B} = \alpha_R/K_R^d + \phi \left(\frac{1}{K_f} - \frac{1}{K_R^\phi} \right). \quad (35)$$

Alternatively, I could say that

$$B = \frac{\alpha_R}{\gamma K_R^d}. \quad (36)$$

I have now determined the physical/mechanical significance of all the coefficients in the poroelastic matrix (22). These results are as general as possible without considering poroelastic symmetries that have less than orthotropic symmetry, while also taking advantage of my assumption that I do typically know (or can often determine) the three directions of the principal axes of symmetry.

Inverting poroelastic compliance

The matrix in (22) is in compliance form and has extremely simple poroelastic behavior in the sense that all the fluid mechanical effects appear only in the single coefficient γ . I can simplify the notation a little more by lumping some coefficients together, combining the 3×3 submatrix in the upper left corner of the matrix in (22) as \mathbf{S} , and defining the column vector \mathbf{b} by

$$\mathbf{b}^T \equiv (\beta_1, \beta_2, \beta_3). \quad (37)$$

The resulting 4×4 matrix and its inverse are now related by:

$$\begin{pmatrix} \mathbf{S} & -\mathbf{b} \\ -\mathbf{b}^T & \gamma \end{pmatrix} = \begin{pmatrix} \mathbf{A} & \mathbf{q} \\ \mathbf{q}^T & z \end{pmatrix}^{-1}, \quad (38)$$

where the elements of the inverse matrix can be shown to be written in terms of drained stiffness matrix $\mathbf{C}^d = \mathbf{C} = \mathbf{S}^{-1}$ by introducing three components: (a) scalar $z = [\gamma - \mathbf{b}^T \mathbf{C} \mathbf{b}]^{-1}$, (b) column vector $\mathbf{q} = z \mathbf{C} \mathbf{b}$, and (c) undrained 3×3 stiffness matrix (*i.e.*, the pertinent one connecting the principal strains to principal stresses) $\mathbf{A} = \mathbf{C} + z \mathbf{C} \mathbf{b} \mathbf{b}^T \mathbf{C} = \mathbf{C}^d + z^{-1} \mathbf{q} \mathbf{q}^T \equiv \mathbf{C}^u$, since \mathbf{C}^d is drained stiffness and $\mathbf{A} = \mathbf{C}^u$ is clearly undrained stiffness by construction. This result is the same as that of Gassmann (1951) for anisotropic porous media, although his results were presented in a form somewhat harder to scan than the form shown here.

Also, note the important fact that the observed decoupling of the fluid effects occurs only in the compliance form (22) of the equations, and never in the stiffness (inverse) form for the poroelasticity equations.

From these results, it is not hard to show that

$$\mathbf{S}^d = \mathbf{S}^u + \gamma^{-1} \mathbf{b} \mathbf{b}^T. \quad (39)$$

This result emphasizes the remarkably simple fact that the drained compliance matrix can be found directly from knowledge of the inverse of undrained compliance, and the still unknown, but sometimes relatively easy to estimate, values of γ , together with the three distinct orthotropic β_i coefficients, for $i = 1, 2, 3$.

TABLE 1. Reuss (R), Voigt (V), and self-consistent effective (*) bulk moduli of various common anisotropic materials (Berryman, 2005): Water ice, cadmium, zinc, graphite, α -quartz, corundum, barium titanate, rutile, aluminum, copper, magnesia, spinel. Full references for the data used in both TABLES 1 and 2 are provided in Berryman (2005). Units of bulk modulus K are GPa.

Material	Symmetry	K_R	K^*	K_V	K_V/K_R
H ₂ O	Hexagonal	8.89	8.89	8.89	1.00
Cd	Hexagonal	48.8	54.7	58.1	1.19
Zn	Hexagonal	61.6	70.9	75.1	1.22
Graphite	Hexagonal	35.8	88.0	286.3	8.00
Al ₂ O ₃	Trigonal	253.5	253.7	253.9	1.002
α -SiO ₂	Trigonal	37.6	37.8	38.1	1.01
TiO ₂	Tetragonal	209	213	218	1.04
BaTiO ₂	Tetragonal	163.1	179.3	186.8	1.15
Al	Cubic	76.3	76.3	76.3	1.00
MgO	Cubic	162.4	162.4	162.4	1.00
MgAl ₂ O ₄	Cubic	196.7	196.7	196.7	1.00
Cu	Cubic	138.0	138.0	138.0	1.00

Deducing coefficients from measurements: Anisotropic example with homogeneous grains

Now, further progress is made by considering the Reuss average again for both of the orthotropic drained and undrained compliances:

$$\frac{1}{K_R^d} \equiv \sum_{i,j=1,2,3} s_{ij}^d, \quad (40)$$

and

$$\frac{1}{K_R^u} \equiv \sum_{i,j=1,2,3} s_{ij}^u. \quad (41)$$

These effective moduli are the Reuss averages of the nine compliances in the upper left 3×3 of the full (including the uncoupled shear components) 6×6 compliance matrix for the two cases, respectively, when the pore fluid is allowed to drain from the porous system, and when the pore fluid is trapped by a jacketing material and therefore undrained.

TABLE 2. Reuss (R), Voigt (V), and self-consistent effective (*) shear moduli of various common materials [see Berryman (2005)]: Water ice, cadmium, zinc, graphite, α -quartz, corundum, barium titanate, rutile, aluminum, copper, magnesia, and spinel. Units of shear modulus G are GPa. The anisotropy parameter $\mathcal{A} \equiv 5\frac{G_V}{G_R} + \frac{K_V}{K_R} - 6$ [from Ranganathan and Ostoja-Starzewski (2008a,b)].

Material	Symmetry	G_R	G^*	G_V	G_V/G_R	\mathcal{A}
H ₂ O	Hexagonal	3.48	3.52	3.55	1.02	0.10
Cd	Hexagonal	22.1	24.3	26.4	1.19	1.14
Zn	Hexagonal	34.1	40.6	44.8	1.31	1.77
Graphite	Hexagonal	9.2	52.6	219.4	23.8	121.0
Al ₂ O ₃	Trigonal	160.7	163.1	165.5	1.03	0.15
α -SiO ₂	Trigonal	41.0	44.0	47.6	1.16	0.81
TiO ₂	Tetragonal	99.5	114.5	124.9	1.26	1.34
BaTiO ₂	Tetragonal	47.4	53.6	59.8	1.26	1.46
Al	Cubic	26.0	26.2	26.3	1.01	0.05
MgO	Cubic	123.9	126.3	128.6	1.04	0.20
MgAl ₂ O ₄	Cubic	98.6	109.0	118.0	1.20	1.00
Cu	Cubic	40.0	46.3	51.3	1.28	1.41

Although the significance of the formula in the anisotropic case is somewhat different now, I find again that

$$\beta_1 + \beta_2 + \beta_3 = \frac{1}{K_R^d} - \frac{1}{K_R^g} = \frac{\alpha_R}{K_R^d}, \quad (42)$$

if I also define a Reuss effective stress coefficient:

$$\alpha_R \equiv 1 - K_R^d/K_R^g, \quad (43)$$

by analogy to the isotropic case. Furthermore, I have

$$\gamma = \frac{\beta_1 + \beta_2 + \beta_3}{B} = \frac{\alpha_R}{K_R^d} + \phi \left(\frac{1}{K_f} - \frac{1}{K_R^g} \right), \quad (44)$$

since I have the rigorous result in this notation (Berryman, 1997) that Skempton's B coefficient (Skempton, 1954) is given by

$$B \equiv \frac{1 - K_R^d/K_R^u}{1 - K_R^d/K_R^g} = \frac{\alpha_R/K_R^d}{\alpha_R/K_R^d + \phi(1/K_f - 1/K_R^g)}. \quad (45)$$

I want to emphasize that all these formulas are rigorous statements based on the earlier anisotropic analysis. The appearance of K_R^d and α_R is not an approximation. In fact it is important now in the anisotropic case (but not in the isotropic cases

considered earlier as long as the grains were also homogeneous) to make this distinction between the Reuss and Voigt averages. Making this choice of notation will help demonstrate useful analogies between the rigorous anisotropic formulas and the isotropic ones. I have prepared the way for these analogies by using the Reuss averages in earlier notation, even though they were mostly redundant in those isotropic examples.

First note that, from (42) and (44), it follows that $\gamma^{-1} = \frac{BK_R^d}{\alpha_R}$ — also see (36). So I can now rearrange (39) to give the formal relationship

$$s_{ij}^d = s_{ij}^u + \frac{BK_R^d}{\alpha_R} \beta_i \beta_j, \quad \text{for } i, j = 1, 2, 3. \quad (46)$$

At this point in the analysis, I know everything needed except for the three coefficients β_i , for $i = 1, 2, 3$. But, by taking appropriate sums of (46), I find that

$$\beta_i = s_{i1}^d + s_{i2}^d + s_{i3}^d - \frac{1}{3K_R^g} = s_{i1}^u + s_{i2}^u + s_{i3}^u - \frac{1}{3K_R^g} + B\beta_i. \quad (47)$$

Rearranging, I find that

$$\beta_i(1 - B) = s_{i1}^u + s_{i2}^u + s_{i3}^u - \frac{1}{3K_R^g}. \quad (48)$$

Formula (45) for the Skempton (1954) coefficient determines B exactly in terms of presumed known quantities. In the present case, the Skempton coefficient B , however, was not assumed to be known, since for homogeneous grains I can compute K_R^d relatively easily, and then B follows since I also know K_R^g . [For the case of heterogeneous or anisotropic grains, the necessary introduction of the additional variable K_R^ϕ requires still more measured data, and it turns out that the next easiest quantity to measure is B itself — as was already shown in the isotropic case.] So, all three β_i 's (which are themselves drained constants) and γ are now precisely determined. All the remaining drained compliances s_{ij}^d can then be found directly from (46). Note that all the steps in this inversion procedure are linear; there was no need to solve any quadratic equation in this formulation of the undrained-to-drained inversion problem. There is also no iteration, and no fitting steps are required in this procedure.

Deducing anisotropic drained constants from undrained: Homogeneous grains and pores

I am now in position to develop the analogy between the isotropic and anisotropic Gassmann (1951) equations for the case of homogeneous grains. In particular, the equation for the suspension modulus in (2) does not change at all. In contrast, the equation for the effective undrained bulk modulus K^u , as shown in both (1) and (3), changes only in that the relationship is now between the Reuss averages K_R^u and K_R^d

of these quantities. This result is completely analogous to (3), and so will not be shown here.

Since the remainder of the argument is virtually identical to the isotropic case, I therefore obtain:

$$K_R^d = \left(\frac{K_R^u}{K_{susp}} - 1 \right) \left[1/K_{susp} - 2/K_R^g + K_R^u/(K_R^g)^2 \right]^{-1}. \quad (49)$$

This formula shows how to invert for drained Reuss bulk modulus K_R^d from knowledge of K_R^u , ϕ , K_f and K_R^g in an anisotropic (up to orthotropic) poroelastic system.

TABLE 3. Data for the principal stiffness coefficients c_{ij} of orthorhombic sulfur (S), Rochelle salt, Benzophenone, and α -Uranium (α -U). All data from Musgrave (2003), but re-expressed in units of GPa.

Stiffness	Sulfur (S)	Rochelle Salt	Benzophenone	α -Uranium
c_{11}	24.0	25.5	107.0	215.0
c_{22}	20.5	38.1	100.0	199.0
c_{33}	48.3	37.1	71.0	267.0
c_{12}	13.3	14.1	55.0	46.0
c_{13}	17.1	11.6	16.9	22.0
c_{23}	15.9	14.6	32.1	107.0

TABLE 4. Data for various measures of bulk modulus K (Voigt, Reuss, and three partial sum moduli) for orthorhombic sulfur (S), Rochelle salt, Benzophenone, and α -Uranium (α -U). All data from Musgrave (2003) [see TABLE 3 here], while the expressions in the main text were used for the computations. All moduli in units of GPa.

Bulk Modulus	Sulfur (S)	Rochelle Salt	Benzophenone	α -Uranium
K_V	20.6	20.1	54.0	114.6
K_R	17.6	19.3	49.2	111.3
K_1	15.2	12.5	55.8	87.9
K_2	10.1	30.6	107.5	113.6
K_3	15.8	23.3	29.6	147.7

Clearly this formula does not yet provide the individual compliance matrix elements s_{ij}^d directly. Nevertheless, Equation (49) was the hardest step in the overall procedure. The rest of the steps follow easily once I have this rigorous result available to use.

To finish the analysis, I make use of the newly computed value of K_R^d , and substitute this number into the formula for B , which in this case is:

$$B = \frac{1 - K_R^d/K_R^u}{1 - K_R^d/K_R^g}. \quad (50)$$

Once I know Skempton coefficient B , this value can be substituted into (48) in order to determine the β_i coefficients for $i = 1, 2, 3$. The remaining coefficient is $\gamma = \alpha_R/BK_R^d$. So I have shown that the critical step in this process was determining the value of the drained Reuss bulk modulus K_R^d .

Deducing anisotropic drained constants from undrained: Heterogeneous grains and pores

One difficulty for heterogeneous grains comes from the additional constant K_R^ϕ that I do not know how to determine independently from the other poroelastic measurements. But this fundamental problem is actually no different for the anisotropic case than it was for the isotropic one, and the solution is also the same. In both cases, I need more information, and in both cases the necessary information will most likely come from our knowledge of the Skempton (1954) coefficient B . If I assume that B can be directly measured (which is plausible, since $B = p_f/p_c$ in the undrained case when a uniform confining pressure is applied to the system), then the problem is completely solved, because B is the key to solving for the coefficients β_i in (48). The only new difficulty is that the terms of the form $1/3K_R^g$ must also be replaced by the partial grain compliance sums $\frac{1}{3\bar{K}_i^g}$, as shown in (30). So I now have

$$\beta_i = s_{i1}^d + s_{i2}^d + s_{i3}^d - \frac{1}{3\bar{K}_i^g} = s_{i1}^u + s_{i2}^u + s_{i3}^u - \frac{1}{3\bar{K}_i^g} + B\beta_i. \quad (51)$$

Rearranging, I find that, for heterogeneous grains, the result is:

$$\beta_i(1 - B) = s_{i1}^u + s_{i2}^u + s_{i3}^u - \frac{1}{3\bar{K}_i^g}. \quad (52)$$

So, I am almost done now, but I still need either to determine the values of the anisotropic grain correction terms $\frac{1}{3\bar{K}_i^g}$, or to find some way of avoiding the necessity of doing so.

In principle, this can be done experimentally by actually performing a test on the porous sample that applies the same pressure inside and outside. Then, measurements of the change in strain in the three orthogonal directions $i = 1, 2, 3$ would provide direct measures of the quantities \bar{K}_i^g needed. So this approach is one that is experimentally feasible.

An alternative that I have not considered so far would be to perform shear tests by applying nonzero deviatoric stress changes (Skempton, 1954; Lockner and Stanchits,

2002). The undrained fluid pressure is given by $p_f = Bp_c = B(-\sigma_m)$, where the mean stress is $\sigma_m = (\sigma_{11} + \sigma_{22} + \sigma_{33})/3$. But, if the σ_{ii} 's are not uniform, then there are also deviatoric stresses present, due to the nonuniformity of the principal stresses.

Triaxial testing geometry

One common example of this type of measurement uses triaxial testing [see Lockner and Stanchits (2002)], where a two-sided confining stress is defined as $\sigma_{22} = \sigma_{33}$, and then the deviatoric stress is determined by

$$\sigma_{dev} \equiv (\sigma_{11} - \sigma_{33})/2. \quad (53)$$

In this situation, the general equation relating undrained pressure to the confining stresses is given by:

$$-p_f = B\sigma_m + 2 \left(A - \frac{1}{3} \right) B\sigma_{dev}, \quad (54)$$

where the only new symbol is the first coefficient A of Skempton (1954).

TABLE 5. Data for the principal stiffness coefficients c_{ij} for $i, j = 1, 2, 3$, as well as c_{44} , of hexagonal minerals: cadmium (Cd), H₂O ice, β -quartz (SiO₂), titanium (Ti), and zirconium (Zr). All data from Simmons and Wang (1971) [entry numbers: 52473, 52563, 52643, 52726, and 52798, respectively], but re-expressed in units of GPa.

Stiffness	Cadmium (Cd)	H ₂ O Ice	β -Quartz	Titanium (Ti)	Zirconium (Zr)
c_{11}	115.30	13.85	116.6	163.9	137.0
c_{33}	51.20	14.99	110.4	181.6	160.7
c_{12}	39.24	7.07	16.7	91.3	75.6
c_{13}	40.22	5.81	32.8	68.9	65.4
c_{44}	20.40	3.19	36.1	47.2	30.1

TABLE 6. Data for various measures of bulk modulus K (Voigt, Reuss, and three partial-sum moduli) for hexagonal minerals: cadmium (Cd), H₂O ice, β -quartz (SiO₂), titanium (Ti), and zirconium (Zr). All data from Simmons and Wang (1971) [see TABLE 5], while the expressions in the main text were used for all the computations. All moduli in units of GPa.

Modulus	Cadmium (Cd)	H ₂ O Ice	β -Quartz	Titanium (Ti)	Zirconium (Zr)
K_V	57.89	8.90	56.47	107.51	94.17
K_R	48.61	8.90	56.37	107.50	94.02
$K_1 = K_2$	143.07	8.94	53.97	109.00	89.58
K_3	20.95	8.82	61.86	104.63	104.36

It is not difficult to show that, in terms of our previous definitions for the triaxial testing geometry, the coefficient A is given precisely by the ratio

$$A \equiv \frac{\beta_1}{\beta_1 + \beta_2 + \beta_3}. \quad (55)$$

For an isotropic system, $A = 1/3$, so this contribution always vanishes in (54). This fact explains why I did not encounter this coefficient before in the analysis. Note that there is no assumption here that the poroelastic system itself is necessarily transversely isotropic. Only the prescribed equality of the two applied transverse stresses, σ_{22} and σ_{33} , is assumed. Then, the formula (54) follows directly from the equations already presented.

Non-triaxial testing geometries

Clearly, it would also be natural to introduce other measures of the β_i coefficients as well, especially if the measurements are not being constrained to the triaxial testing configuration. So I might imagine that three such coefficients could be measured according to:

$$-p_f = B \left[\sigma_m + \sum_i A_i (\sigma_{ii} - \sigma_m) \right], \quad (56)$$

where

$$A_i = \frac{\beta_i}{\beta_1 + \beta_2 + \beta_3}, \quad (57)$$

for $i = 1, 2, 3$. In general, no more than two of these A_i coefficients can be independent since $\sum_{i=1,2,3} A_i \equiv 1$. But, for general testing configurations, there could be two useful and distinct measurements to be gathered from deviatoric response testing, although only one was available in the triaxial testing configuration.

In order to be able to deduce the values of the β_i 's from the A_i 's, I need to know the value of the sum $\beta_1 + \beta_2 + \beta_3 = \gamma B$. I also needed to know the value of B to determine any of the A_i 's, but the value of γ is harder to determine independently. The values of K_R^u and the total K_R^g are both usually easier to determine, so it is likely enough information is available to compute the β_i sum this way:

$$\beta_1 + \beta_2 + \beta_3 = \frac{\frac{1}{K_R^u} - \frac{1}{K_R^g}}{1 - B} = \gamma B. \quad (58)$$

If the β_i sum has been computed using (58), then clearly I also have

$$\beta_i = A_i \left(\frac{\frac{1}{K_R^u} - \frac{1}{K_R^g}}{1 - B} \right). \quad (59)$$

Once I have computed the β_i 's, I also find (if I want to, although it is not usually critical information) the values of the partial sums of the grain Reuss modulus:

$$\frac{1}{3K_i^g} \equiv s_{i1}^u + s_{i2}^u + s_{i3}^u - \beta_i(1 - B). \quad (60)$$

This additional information is therefore available if needed for some other reason such as determining how well-stirred the particles composing a given granular medium might be.

Deducing anisotropic drained constants from undrained for very heterogeneous porous media

At this point I have determined a data processing scheme that would provide all the drained constants for a poroelasticity system from measurements of the undrained constants. In the example of the preceding subsection, I needed to broaden the meaning of the undrained set of constants to include the Skempton A_i coefficients, which were not needed in earlier parts of the paper. But they could nevertheless be computed from the information found earlier, since I did show how to compute all the β_i 's directly, and these coefficients provide just the information that I would need for determining these values from (57).

In realistic data collection situations, especially those involving field data, my previous assumptions concerning the nature and orientations of the constituent grains of the granular porous medium may sometimes – perhaps most times – be too idealized. Nevertheless, it is the case that the equations of poroelasticity never become any more complex than those shown here. What does change is the interpretation of the directional grain moduli. In the worst case scenario, equation (60) needs to be replaced by an equation of the same form, namely:

$$\frac{1}{3K_i^*} = s_{i1}^u + s_{i2}^u + s_{i3}^u - \beta_i(1 - B). \quad (61)$$

Measurements are exactly as before, but the interpretation of the resulting constant estimator K_i^* becomes that of an effective medium bulk modulus, *i.e.*, one that is (or at least could be) dependent on the directions $i = 1, 2, 3$ of measurement. Effective medium theories for random polycrystals generally assume [see Berryman (2005)] that the anisotropic grains are perfectly randomly oriented. Of course, this may not be true in practice. But to do a better job of predicting the outcome of experiments in situations where grain orientations are not perfectly random, I need information about these deviations from perfect randomness. In the present context, the information would come in the form of these measured constants K_i^* . Some effort could then be expended in showing how such moduli might arise if the constituents' nature and volume fractions are known. But in the absence of such knowledge, these constants are sufficient to analyze other results of most experiments of interest in poroelasticity.

To provide different ideas about how important the anisotropy, and the random orientation of the constituents might be in a few cases, TABLES 1 and 2 show some quantitative examples based on results of Berryman (2005) and Ranganathan and Ostoja-Starzewski (2008a,b). TABLES 3 and 4, respectively, provide input data for the types of orthorhombic solids (Musgrave, 2003), and the results for the Voigt,

Reuss, and directional measures of bulk moduli for these particular materials. Note the significant finding that the directional moduli do not have to stay within the values set by the Voigt and Reuss estimators.

Tables 5–9 show similar results for selected data taken from the compendium assembled by Simmons and Wang (1971).

TABLE 7. Data for the principal stiffness coefficients c_{ij} for $i, j = 1, 2, 3$ and c_{44} of cubic symmetry minerals: aluminum (Al), copper (Cu), magnesia (MgO), and spinel (MgAl_2O_4). All data from Simmons and Wang (1971) [entry numbers: 10089, 10385, 10902, and 11877, respectively], but re-expressed in units of GPa.

Stiffness	Aluminum (Al)	Copper (Cu)	Magnesia (MgO)	Spinel (MgAl_2O_4)
c_{11}	107.30	170.98	297.08	298.57
c_{12}	60.80	123.99	95.36	153.72
c_{44}	28.30	75.45	156.13	157.58

TABLE 8. Data for various measures of bulk modulus K (Voigt, Reuss, and three partial-sum moduli) for cubic symmetry minerals: aluminum (Al), copper (Cu), magnesia (MgO), and spinel (MgAl_2O_4). All data from Simmons and Wang (1971) [see TABLE 7], while the expressions in the main text were used for all the computations. All moduli in units of GPa. Clearly, all the pertinent bulk moduli for each material are the same (*i.e.*, $K_V = K_R = K_1 = K_2 = K_3$, even though these cubic symmetry minerals are not isotropic).

Bulk Modulus	Al	Cu	MgO	MgAl_2O_4
$K_V = K_R = \dots$	76.3	139.65	162.6	202.00

SUMMARY AND CONCLUSIONS

There have been a great many experiments done on poroelastic systems through the years, and many attempts to measure complete poroelastic data sets. The work summarized here is designed to make this process easier by removing the need (whenever possible) for tedious fitting routines that have traditionally been used to find the pertinent drained constants for the measured fluid-saturated and undrained systems. It is of some real scientific importance to have methods like those treated here, because it is a well-known fact that the presence of the pore-fluid can alter the nature of the points of contact between neighboring grains, and therefore alter the values of the “drained” constants that were sought here and found via the methods developed for this purpose. Different values of the “drained” constants might be obtained if all the fluid is physically drained out of the system, so it is effectively “dry” rather than merely “drained” (*i.e.*, in the sense of pore-fluid having the capability of moving in and out of the boundaries as would happen in the absence of jacketing material). In

the case of a fully dry system, the grain-to-grain contacts may act very differently than they do when saturated with certain fluids. At the very least, it could be important to check experimentally whether these constants are different or not in a variety of systems, and the present analysis will permit such studies to move forward.

One especially interesting aspect of the analysis presented is that in no case did the solution of any of the problems treated involve any analysis more complicated than solving a linear equation. There are no quadratic equations solved in this paper, and none that needed to be solved. The hardest calculation in the paper is the implicit inversion of a 3×3 matrix when the real data are poroelastic stiffnesses, rather than compliances. [Note: Matrix inversion requires only the calculation of various determinants, but not the solution of any quadratic or cubic equations. These additional difficulties can be avoided unless I also want or need to find the eigenvalues of the matrix. But this step is unnecessary in the work described here.] This situation does occur in practice whenever the elastic/poroelastic data are obtained using wave propagation methods. Then, the actual data have the form $v = \sqrt{c/\rho}$, where v is a wave speed, c is a stiffness or combination of stiffnesses, and ρ is the inertial density. A complete set of the stiffnesses for the principal stresses and strains is needed for the analysis because I require compliance data, and to obtain a complete set of compliance data from stiffness data, I also need a complete set of the corresponding stiffness data. All the elements of the undrained 3×3 compliance matrix for the principal stresses and strains must be known in order to proceed with the described analysis.

TABLE 9. Reuss (R) and Voigt (V) shear moduli of various common hexagonal and cubic materials (Simmons and Wang, 1971): cadmium, β -quartz, titanium, zirconium, aluminum, copper, magnesia, and spinel. Units of shear modulus G are GPa. All the formulas needed to compute the various effective moduli from the stiffness coefficients are given in Berryman (2005). The anisotropy parameter $\mathcal{A} \equiv 5\frac{G_V}{G_R} + \frac{K_V}{K_R} - 6$ [from Ranganathan and Ostoja-Starzewski (2008a,b)].

Material	Symmetry	G_R	G_V	G_V/G_R	\mathcal{A}
Cd	Hexagonal	22.1	26.4	1.197	1.174
SiO ₂	Hexagonal	3.48	3.55	1.025	0.125
Ti	Hexagonal	34.1	44.8	1.31	0.154
Zr	Hexagonal	32.54	33.40	1.03	0.132
Al	Cubic	26.04	26.28	1.009	0.045
Cu	Cubic	40.04	54.67	1.365	1.825
MgO	Cubic	128.06	134.02	1.047	0.235
MgAl ₂ O ₄	Cubic	107.17	123.52	1.152	0.76

The analysis has been restricted to systems having orthotropic poroelastic symmetry or higher. Lower symmetry systems might also be studied, but I purposely

avoided them here because for such systems it is harder to know for sure from experimental data when you have determined the true axes of symmetry. Also, in such cases of orthotropic symmetry or higher, the system of equations to be studied is substantially reduced because there is no coupling of the fluid effects to the shear components associated with the strains e_{23} , e_{31} , e_{11} , or the stresses σ_{23} , σ_{31} , σ_{12} . Shear effects are not ignored altogether however, as there are well-known shearing mechanisms in poroelastic media associated with the Skempton (1954) coefficient A [also see Lockner and Stanchits (2002)]. These effects were studied here in some detail, and were found to be very useful in accomplishing our main goals, since they provided a necessary mechanism for measuring some otherwise difficult to measure off-diagonal terms in the poroelastic equations.

I conclude that this analysis has been successful in solving the problem of obtaining drained constants from undrained constants in all the cases considered. The chosen set of cases (orthotropic or higher symmetry) is not very restrictive from a practical point of view, as the great majority of poroelastic systems studied in practice usually have hexagonal (transversely isotropic) symmetry or higher, and therefore are all explicitly included within the range of the present analyses.

ACKNOWLEDGMENTS

I thank Seiji Nakagawa and Leon Thomsen for helpful comments on the work. I thank Adam Halpert and Mandy Man Chu Wong for useful suggestions that improved the manuscript.

REFERENCES

- Barenblatt, G. I. and Y. P. Zheltov, 1960, Fundamental equations of filtration of homogeneous liquids in fissured rocks: *Sov. Phys. Dokl.*, **132**, 545–548.
- Berryman, J. G., 1997, Transversely isotropic elasticity and poroelasticity arising from thin isotropic layers, *in* Teng, Y.-C., E.-C. Shang, Y.-H. Pao, M. H. Schultz, and A. D. Pierce, eds., *Theoretical and Computational Acoustics 1997*, 457–474, World Scientific, Newark, NJ.
- , 2005, Seismic waves in rocks with fluids and fractures: *Journal of the Mechanics and Physics of Solids*, **53**, 2141–2173.
- Berryman, J. G. and G. W. Milton, 1991, Exact results for generalized gassmann’s equations in composite porous media with two constituents: *Geophysics*, **56**, 1950–1960.
- Berryman, J. G. and S. R. Pride, 2002, Models for computing geomechanical constants of double-porosity materials from the constituents’ properties: *Journal of Geophysical Research*, **107**, 2052–1–2052–15.
- Biot, M. A. and D. G. Willis, 1957, The elastic coefficients of the theory of consolidation: *ASME Journal of Applied Mechanics*, **24**, 594–601.

- Brown, R. J. S. and J. Korrington, 1975, On the dependence of the elastic properties of a porous rock on the compressibility of the pore fluid: *Geophysics*, **40**, 608–616.
- Cheng, A. H.-D., 1997, Material coefficients of anisotropic poroelasticity: *International Journal of Rock Mechanics*, **34**, 199–205.
- Gassmann, F., 1951, On elasticity of porous media, *in* Pelissier, M. A., H. Hoerber, N. van de Coevering, and I. F. Jones, eds., *Classics of Elastic Wave Theory*, volume **24**, 389–407, Society of Exploration Geophysicists, Tulsa, Oklahoma.
- Gurevich, B., D. Makarynska, and M. Pervukhina, 2009, Ultrasonic moduli for fluid-saturated rocks: Mavko-Jizba relations rederived and generalized: *Geophysics*, **74**, N25–N30.
- Hill, R., 1952, The elastic behaviour of crystalline aggregate: *Proceedings of the Physical Society of London*, **A65**, 349–354.
- Lockner, D. A. and S. A. Stanchits, 2002, Relations between drained and undrained moduli in anisotropic poroelasticity: *Journal of Geophysical Research*, **107**, 2353–1–2353–14.
- Musgrave, M. J. P., 2003, *Crystal Acoustics: Introduction to the Study of Elastic Waves and Vibrations in Crystals*: Acoustical Society of America, New York.
- Ranganathan, S. I. and M. Ostojca-Starzewski, 2008a, Universal elastic anisotropy index: *Physical Review Letters*, **101**, 055502.
- , 2008b, Universal elastic anisotropy index: *Physical Review B*, **77**, 214308.
- Reuss, A., 1929, Berechnung der Fließgrenze von Mischkristallen: *Z. Angew. Math. Mech.*, **9**, 55.
- Rice, J. R. and M. P. Cleary, 1976, Some basic stress diffusion solutions for fluid-saturated elastic porous media with compressible constituents: *Reviews of Geophysics and Space Physics*, **14**, 227–241.
- Simmons, G. and H. Wang, 1971, *Single Crystal Elastic Constants and Calculated Aggregate Properties: A Handbook*: The M.I.T. Press, Cambridge, Massachusetts.
- Skempton, A. W., 1954, The pore-pressure coefficients a and b : *Géotechnique*, **4**, 143–147.
- Stoll, R. D., 1974, Acoustic waves in saturated sediments, *in* *Physics of Sound in Marine Sediments*, 19–39, Plenum, New York.
- Thigpen, L. and J. G. Berryman, 1985, Mechanics of porous elastic materials containing multiphase fluid: *International Journal of Engineering Science*, **23**, 1203–1214.
- Voigt, W., 1928, *Lehrbuch der Kristallphysik*: Teubner, Leipzig.
- Wang, H. F., 2000, *Theory of Linear Poroelasticity with Applications to Geomechanics and Hydrogeology*: Princeton University Press, Princeton, NJ.
- Wood, A. W., 1955, *A Textbook of Sound*: Bell, London, England.
- Zhu, X. and G. A. McMechan, 1990, Direct estimation of the bulk modulus of the frame in a fluid-saturated elastic medium by Biot theory: 60th International Meeting, Expanded Abstracts, 787–790, Society of Exploration Geophysicists, Tulsa, Oklahoma.