

Stanford Exploration Project Sponsors' Meeting 

Death Valley, California, March 6–9, 2006

**SEISMIC WAVE PROPAGATION IN ROCKS
WITH FLUIDS AND FRACTURES**

Speaker: James G. Berryman

University of California

Lawrence Livermore National Laboratory

Livermore, CA 94551-9900

OUTLINE



- Anisotropy Due to Fractures
 - Sayers-Kachanov method
 - Thomsen parameters and Rayleigh waves
- Deconstruction
 - Seismic reflection data
 - Surface wave data
- Gassmann's Equations and Mavko-Jizba
- Discussion and Conclusions
- References

STIFFNESS VERSUS COMPLIANCE



The isotropic stiffness matrix (inverse of the compliance matrix) for an elastic material is often written as $C =$

$$\begin{pmatrix} \lambda + 2G & \lambda & \lambda & & & & \\ \lambda & \lambda + 2G & \lambda & & & & \\ \lambda & \lambda & \lambda + 2G & & & & \\ & & & G & & & \\ & & & & G & & \\ & & & & & G & \end{pmatrix}$$

where λ and G are the two Lamé parameters,

G is shear modulus, and $K = \lambda + 2G/3$ is bulk modulus.

ANISOTROPY DUE TO FRACTURES (1)



The isotropic compliance matrix (inverse of the stiffness matrix) for an elastic material is often written as $S =$

$$\begin{pmatrix} \frac{1}{E} & -\frac{\nu}{E} & -\frac{\nu}{E} & & & & \\ -\frac{\nu}{E} & \frac{1}{E} & -\frac{\nu}{E} & & & & \\ -\frac{\nu}{E} & -\frac{\nu}{E} & \frac{1}{E} & & & & \\ & & & \frac{1}{G} & & & \\ & & & & \frac{1}{G} & & \\ & & & & & \frac{1}{G} & \end{pmatrix}$$

where E is Young's modulus, ν is Poisson's ratio, and $G = E/2(1 + \nu)$ is the shear modulus.

ANISOTROPY DUE TO FRACTURES (2)



In the following discussion, I will assume that all the fractures/cracks are in the form of penny-shaped cracks. These are defined as oblate spheroids, having round and flat holes, circular in cross-section with area $A = \pi b^2$, and volume $V_c = 4\pi ab^2/3$, or $V_c = 4\pi\alpha b^3/3$, where $\alpha \equiv a/b$ is the aspect ratio. We assume $\alpha = a/b \ll 1$, so the crack porosity $\phi = V_c/V \ll 1$.

ANISOTROPY DUE TO FRACTURES (3)



Sayers and Kachanov (1991) show that corrections to the isotropic matrix S_{ij} , caused by low crack densities ($\rho \ll 1$), can be written as

$$\Delta \left(\frac{1}{G} \right) = 4\eta_2 \rho / 3,$$

$$\Delta \left(-\frac{\nu}{E} \right) = 2\eta_1 \rho / 3,$$

$$\Delta \left(\frac{1}{E} \right) = 2(\eta_1 + \eta_2) \rho / 3,$$

where η_1 and η_2 are parameters to be found from EMT.

ANISOTROPY DUE TO FRACTURES (4)



Thus, in the isotropic case, we have

$$\Delta S_{ij} = (2\rho/3) \times$$

$$\begin{pmatrix} (\eta_1 + \eta_2) & \eta_1 & \eta_1 & & & & \\ \eta_1 & (\eta_1 + \eta_2) & \eta_1 & & & & \\ \eta_1 & \eta_1 & (\eta_1 + \eta_2) & & & & \\ & & & 2\eta_2 & & & \\ & & & & 2\eta_2 & & \\ & & & & & 2\eta_2 & \\ & & & & & & \end{pmatrix}.$$

ANISOTROPY DUE TO FRACTURES (6)



For vertical cracks whose axis of symmetry is randomly oriented in the xy -plane, we have another anisotropic medium whose correction matrix is

$$\Delta S_{ij} = \rho \times$$

$$\begin{pmatrix} (\eta_1 + \eta_2) & \eta_1 & \eta_1/2 & & & & \\ \eta_1 & (\eta_1 + \eta_2) & \eta_1/2 & & & & \\ \eta_1/2 & \eta_1/2 & 0 & & & & \\ & & & \eta_2 & & & \\ & & & & \eta_2 & & \\ & & & & & 2\eta_2 & \\ & & & & & & \end{pmatrix}.$$

ANISOTROPY DUE TO FRACTURES (7)



Examples of the values of the η 's found from various effective medium theories are:

<u><i>EMT</i></u>	<u>η_1</u>	<u>η_2</u>
<i>NI</i>	-0.000216	0.0287
<i>DS</i>	-0.000216	0.0290
<i>CPA</i>	-0.000258	0.0290
<i>SC</i>	-.0000207	0.0290

THOMSEN PARAMETERS (1)



For the case of randomly oriented vertical fractures, two of the Thomsen parameters can be expressed as:

$$\gamma \equiv \frac{C_{66} - C_{44}}{2C_{44}} = -\eta_2 \rho \frac{E}{4(1+\nu)} = -\eta_2 \rho \frac{G}{2}$$

$$\epsilon \equiv \frac{C_{11} - C_{33}}{2C_{33}} \simeq -\eta_2 \rho \frac{G}{1-\nu}.$$

The remaining Thomsen parameter δ , which is the one that determines the degree of anellipticity in angular dependence of the wave speeds is given exactly by $\delta = \epsilon$, which means there is no deviation from ellipticity.

THOMSEN PARAMETERS (2)



For the case of horizontal fractures, the same two Thomsen parameters can be expressed as:

$$\gamma \equiv \frac{C_{66} - C_{44}}{2C_{44}} = \eta_2 \rho G$$

$$\epsilon \equiv \frac{C_{11} - C_{33}}{2C_{33}} \simeq \eta_2 \rho \frac{2G}{1-\nu}.$$

Note that these results both differ exactly by a factor of -2 from the previous results for randomly oriented vertical fractures. This fact can be easily understood in terms of the Sayers and Kachanov style of analysis.

RAYLEIGH WAVE SPEED



For a transversely isotropic medium with vertical axis of symmetry (which is true of both the cases described so far), the Rayleigh surface wave has a speed determined by the following equation:

$$\frac{1}{16}q^3 - \frac{1}{2}q^2 + \left(\frac{3}{2} - \frac{C_{66}}{C_{11}}\right)q + \left(\frac{C_{66}}{C_{11}} - 1\right) = 0,$$

where $q \equiv v_R^2/v_s^2$ and $v_s^2 = C_{66}/\rho_0$,

with ρ_0 being the inertial mass density of the medium.

Recall that $C_{66} = C_{44}(1 + 2\gamma)$ and that $C_{11} = C_{33}(1 + 2\epsilon)$

in terms of Thomsen parameters.

GASSMANN'S EQUATIONS (1)



$$K_u = K_d + \frac{\alpha^2}{(\alpha - \phi)/K_m + \phi/K_f},$$

where K_u is the undrained bulk modulus, K_d is the drained bulk modulus, K_m is the mineral (or solid) modulus, K_f is the pore fluid bulk modulus, ϕ is the porosity, and $\alpha = 1 - K_d/K_m$.

Rearranging into compliance form, we have

$$\frac{1}{K_u} - \frac{1}{K_d} = -\frac{\alpha}{K_d} \times \left[1 + \frac{K_d \phi}{K_f \alpha} \left(1 - \frac{K_f}{K_m} \right) \right]^{-1}.$$

Also, porosity $\phi = \frac{4\pi a}{3b} \frac{Nb^3}{V} = \frac{4\pi a}{3b} \rho$.

GASSMANN'S EQUATIONS (2)



Compliance correction matrix for fluid inclusions:

$$\Delta S_{ij} = -\gamma^{-1} \begin{pmatrix} \beta_1^2 & \beta_1\beta_2 & \beta_1\beta_3 & & & \\ \beta_1\beta_2 & \beta_2^2 & \beta_2\beta_3 & & & \\ \beta_1\beta_3 & \beta_2\beta_3 & \beta_3^2 & & & \\ & & & 0 & & \\ & & & & 0 & \\ & & & & & 0 \end{pmatrix}$$

The fluid effects (K_f) appear only in the overall factor

γ . The coefficients β_i , $i = 1, 2, 3$, satisfy a sumrule

of the form $\beta_1 + \beta_2 + \beta_3 = 1/K_d - 1/K_m \equiv \alpha/K_d$.

K_d is the drained bulk modulus. K_m is the mineral (solid) modulus.

GASSMANN CORRECTIONS TO SAYERS-KACHANOV FORMULAS



With $\rho = Nr^3/V$ being the crack density parameter, and η_2 being the Sayers-Kachanov parameter that perturbs the shear compliance, we have

$$\Delta S_{ij} \simeq \frac{2\eta_2\rho}{3} \times \begin{pmatrix} (1 - K_f/K_m) & 0 & 0 & 0 & 0 & 0 \\ 0 & (1 - K_f/K_m) & 0 & 0 & 0 & 0 \\ 0 & 0 & (1 - K_f/K_m) & 0 & 0 & 0 \\ 0 & 0 & 0 & (1 - K_f/K_m) & 0 & 0 \\ 0 & 0 & 0 & 0 & (1 - K_f/K_m) & 0 \\ 0 & 0 & 0 & 0 & 0 & (1 - K_f/K_m) \end{pmatrix}$$

MAVKO-JIZBA REDERIVED



It is now easy to show that

$$\frac{1}{K_u} - \frac{1}{K_d} \equiv \Delta \left(\frac{1}{K_u} \right) = 2\eta_2\rho(1 - K_f/K_m)$$

and

$$\frac{1}{G_u} - \frac{1}{G_d} \equiv \Delta \left(\frac{1}{G_u} \right) = \frac{2}{5} \left(\frac{1}{G_{eff}^r} \right) + \frac{3}{5} \times 0$$

where

$$\Delta \left(\frac{1}{G_{eff}^r} \right) = 4\eta_2\rho(1 - K_f/K_m)/3$$

So

$$\Delta \left(\frac{1}{G_u} \right) = \frac{4}{15} \Delta \left(\frac{1}{K_u} \right).$$

CONCLUSIONS



- The Sayers and Kachanov (1991) approach has some powerful advantages for both forward and inverse modeling in fractured systems, especially when used in conjunction with measured Thomsen parameters.
- For a given material (e.g., quartz) and a given crack shape (e.g., penny-shaped), η_1 and η_2 can be computed once and for all.
- Measured Thomsen parameters can then be inverted for crack density.
- Incorporating fluid dependence rigorously into this problem is easy using the Sayers-Kachanov parameters.

REFERENCES (1)



- J. G. Berryman, 1995, Mixture theories for rock properties: in *American Geophysical Union Handbook of Physical Constants*, edited by T. J. Ahrens, AGU, New York, pp. 205–228.
- J. G. Berryman, 2005, Bounds and self-consistent estimates for elastic constants of random polycrystals with hexagonal, trigonal, and tetragonal symmetries: *J. Mech. Phys. Solids* **53**(10), 2141–2173.
- J. G. Berryman, 2006, Seismic waves in rocks with fluids and fractures: **SEP-124**.

REFERENCES (2)



- V. Grechka, 2005, Penny-shaped fractures revisited: *Stud. Geophys. Geod.*, **49**, 365–381.
- V. Grechka and M. Kachanov, 2006, Effective elasticity of fractured rocks: *The Leading Edge*, **25**, 152–155.

REFERENCES (3)



- C. M. Sayers and M. Kachanov, 1991, A simple technique for finding effective elastic constants of cracked solids for arbitrary crack orientation statistics: *Int. J. Solids Struct.*, **27**, 671–680.
- R. W. Zimmerman, 1991, *Compressibility of Sandstones*, Elsevier, Amsterdam.

REFERENCES (4)



- R. Jones, 1958, In situ measurement of the dynamic properties of soil by vibration methods: *Geotechnique* **8**, 1–21.
- H. P. Bucker, J. A. Whitney, and D. L. Keir, 1964, Use of Stoneley waves to determine the shear velocity in ocean sediments: *J. Acoust. Soc. Am.* **36**, 1595–1596.

ACKNOWLEDGMENT



This work was performed under the auspices of the U.S. Department of Energy (DOE) by the University of California, Lawrence Livermore National Laboratory under contract No. W-7405-ENG-48 and supported specifically by the Geosciences Research Program of the DOE Office of Basic Energy Sciences, Division of Chemical Sciences, Geosciences and Biosciences. All support of the work is gratefully acknowledged.