Stacking operators

Many geophysical algorithms can be cast in the form of a summation over some trajectory in a 2-D space. Familiar examples are NMO-stack, Kirchhoff migration and LMO-stack. In an earlier chapter ?? we defined moveout operators that performed NMO, LMO etc. All that we need to implement the desired algorithms is to combine these moveout operators with a stacking operator that sums over one dimension. For example NMO-stack is NMO followed by summation over the offset dimension. In our C++ classes all of these stacking operators can be coded using a chain of a moveout operator and a stacking operator `fopStack` (see man page ??).

There is no "official" definition of which operator of an operator pair is the operator itself and which is the adjoint. We like to think of the modeling operation itself as *the* operator. In this case the forward operation for NMO-stack is to begin from a model that is the stacked zero-offset trace and spray this trace to all offsets. The adjoint operation is the common-midpoint stacking procedure. On the other hand, the industry machinery keeps churning away at many processes that have well-known names, so people often think of one of them as *the* operator. Industrial data-processing operators are typically adjoints to modeling operators. In this document we always try to define the forward operator as the modeling operator.

LINEAR MOVEOUT AND STACKING

[1]The linear moveout and stacking of a data space is done by the `fopLMOstk` operator. This operator is constructed as a chain of two operators: `fopLMO` and `fopStack`. The adjoint method takes a CMP gather as input, does a linear moveout of the data and finally stacks it. The header file `foplmostk.h` (page 2) shows how the class is define and `foplmostk` (page 2) implements the constructors. Figure 1 shows an LMO stacked CMP gather.

```
class fopLMOstk : public fopChain {
  public:

    // Contructors for fopNMOstk
    // Take time Axis, offset Axis, and slowness (1./vel)
    // parameter, as either a value or an array of
    // values.
    fopLMOstk(Axis &, Axis &, float);
    fopLMOstk(Axis &, Axis &, float a[]);
```

[1]Hector Urdaneta

```
};


fopLMOstk::fopLMOstk(Axis & t, Axis & x, float s) {

num=2;
ops = new foperator*[2];
ops[0] = new fopLMO( t, x, s );
ops[1] = new fopStack( x, 1);

}
fopLMOstk::fopLMOstk(Axis & t, Axis & x, float s[]) {

num=2;
ops = new foperator*[2];
ops[0] = new fopLMO( t, x, s );
ops[1] = new fopStack( x, 1);

}
```



Figure 1: A common midpoint gather before (left) and after (right) LMO stacking at water velocity. stacking-wglmostk [NR]

NMO AND STACK

[2] NMO stack is the process of applying normal moveout to all the traces in a CMP gather and then summing the traces. We implement NMO stack as a composition of two previously defined operators, the NMO operator "fopNMO" and the stacking operator "fopStack". To avoid the nuisance of having to create two operators each time we want to perform NMO and stack we create a new class, derived from the

[2]Dave Nichols

fopchain class, that builds a chain of the two operators for us. The code for this is almost exacty the same as the code for the LMO stack class (page 2) except that the fopLMO operator is replaced by a `fopNMO` operator (page ??). Note that, as usual, the forward operation is the modeling operation. The adjoint is the familiar CMP stack.

Let $\mathbf{A}$ denote NMO-stack modeling (modeling from one zero offset stack trace to a full gather with hyperbolic moveout), and let the NMO-stack be defined by invoking the adjoint of the operator. Figure 2 shows a model trace $\mathbf{x}$ on the left and the result of applying the forward operator $\mathbf{A}\,\mathbf{x}$ on the right, this is our synthetic CMP gather, $\mathbf{y}$.



Figure 2: Left frame = input, right frame = modeling. stacking-stackout [NR]

Figure 3 shows the result of adjoint processing on the synthetic CMP gather. The left frame is $\mathbf{A}'\mathbf{y} = \mathbf{A}'\mathbf{A}\mathbf{x}$; we have not recovered our input model, $\mathbf{x}$, because the NMO-stack operator is not unitary. The right frame shows the result of modeling the processed trace $\mathbf{A}\,\mathbf{A}'\,\mathbf{y}$.

We can use a least-squares inverse solver to improve on the adjoint processing. This procedure minimizes $||\mathbf{A}\,\mathbf{x} - \mathbf{y}||^2$. Figure 4 shows the true model and several iterations of an iterative inverse procedure. After ten iterations the exact result has been recovered.

In Figure 5 the result of modeling the inverted result is shown, it completeley recovers the input to the inversion process. It is interesting to contrast this result with the inversion of the NMO operator in section ??. In that inversion we observed a large null space in the operator and the original model was not recovered. One major reason that this does not happen with NMO-stack is that we have reduced the number of variables in the model by a factor of twenty (the number of offsets we stack over).



Figure 3: Left frame = adjoint processing, right frame = adjoint processing + modeling. stacking-stackadj [NR]



Figure 4: Iterations of inverse processing stacking-stackiters [NR]



Figure 5: Left frame = inverse processing, right frame = inverse processing + modeling stacking-stackinv [NR]

KIRCHHOFF OPERATOR

[3]The Kirchhoff poststack operator (Kirchhoff moveout + Stack over offset) is implemented as a composition of two previously defined operators, the KMO operator `fopKMO` and the stacking operator `fopStack`. To avoid the nuisance of having to create two operators each time we want to perform KMO and Stack, we derive a new class `fopKMOstksingle`, from class `fopChain`. For convenience we create an intermediate class `fopKMOstksingle`, that handles only the moveout and stack for a single midpoint gather (or cube). More complicated output geometries, such as poststack 2-D panels or 3-D cubes, produce their operators by chaining the single gather operator.

```
class fopKMOstksingle : public fopChain {
  public:

    // Contructors for fopKMOstk
    // Take time Axis, offset Axis, midpoint Axis and slowness (1./vel)
    // parameter, as either a value or an array
    // values.
    fopKMOstksingle( Axis &, Axis &, float m, float a);
    fopKMOstksingle( Axis &, Axis &, float m, float a[]);

};
```

All that is required to implement this new class is to write a constructor that builds the two separate operators and stores them internally in the `fopChain` class. Application of the two operators forward and adjoint is handled by the parent class so they can inherit its behavior. We do not need to reimplement the code.

```
#include <fopkmostksingle.h>
```

[3]Martin Karrenbach

```
#include <fopkmo.h>
#include <fopstack.h>

// Operator to do KMO and stack (as adjoint) on a single trace.

fopKMOstksingle::fopKMOstksingle(Axis & t,Axis & x, float m, float s) {

  num = 2;
  ops = new foperator*[num];
  ops[0] = new fopKMO( t, x, s ,m );
  ops[1] = new fopStack( x, 1);
}

fopKMOstksingle::fopKMOstksingle(Axis & t,Axis & x, float m ,float s[]) {

  num = 2;
  ops = new foperator*[num];
  ops[0] = new fopKMO( t, x, s ,m );
  ops[1] = new fopStack( x, 1);
}
```

Let $\mathrm{KMOSTK_s}$ denote Kirchhoff modeling from one zero-offset trace to a full gather with hyperbolic moveout. By invoking the adjoint the operator will sum all moved-out traces into a single stacked trace. Thus `fopKMOstksingle` performs the following operation on some given input data set:

$$\mathrm{KMOSTK_s} = \mathrm{STACK}^t \quad \mathrm{KMO} \tag{1}$$

What we consider the normal Kirchhoff stack operator is here the adjoint composite operator $\mathrm{KMOSTK_S}^t$.

Poststack Kirchhoff Operator

The previously introduced class `fopKMOstksingle` can be used for building the more complicated operator which models or migrates a whole poststack panel. Again we chain operators which loop over the midpoint axes and sum the data.

The poststack Kirchhoff operator needs three axes to work on: the time axis, the unmigrated midpoint axis and the migrated midpoint axis. We construct it in the familiar manner:

```
class fopKMOstk : public fopChain {
  public:

    // Contructors for fopKMOstk
    // Take time Axis, offset Axis, midpoint Axis and slowness (1./vel)
    // parameter, as either a value or an array
    // values.
    fopKMOstk( Axis &, Axis &, Axis &, float a);
    fopKMOstk( Axis &, Axis &, Axis &, float a[]);

};
```

The actual work is done in the following operator chain:

$$\mathrm{KIRCH} = \mathrm{KMOSTK_s} \quad \mathrm{MERGE}^t \tag{2}$$

The forward input space is the "time–migrated midpoint" space. We introduce a new dimension the "unmigrated midpoint" axis, which will contain our modeling results.

An operator array is constructed from the input space, with each subspace containing one midpoint. Each of those subspaces is moved out and stacked using `fopKMOstksingle`. The final step is the stack over migrated midpoint axis to obtain the output section. The output is "time–unmigrated midpoint" space. The forward operation thus implements a Kirchhoff modeling process. The adjoint operation is to start with "time" and "unmigrated midpoint" space and applying the adjoint operator chain, ending up with the "time" and "migrated midpoint" space, a migrated dataset.

```
fopKMOstk::fopKMOstk(Axis & t,Axis & m, Axis & x, float s) {

   // make an array of kmostack operators
   fopArray * kmostkops = new fopArray( 1, m.length );

   for ( int i=0; i<m.length; i++ ){
       fopKMOstksingle * kmostack = new fopKMOstksingle( t, x, m.value(i), s );
       kmostkops->set( 0, i, kmostack );
   }
   fopMerge   * mergeop   = new fopMerge( m );
   fopAdjoint * makepanel = new fopAdjoint( mergeop );

   num = 2;
   ops = new foperator*[num];
   ops[0] = kmostkops;
   ops[1] = makepanel;
}
fopKMOstk::fopKMOstk(Axis & t,Axis & x, Axis & m ,float s[]) {

   // make an array of kmostack operators
   fopArray * kmostkops = new fopArray( 1, m.length );

   for ( int i=0; i<m.length; i++ ){
       fopKMOstksingle * kmostack = new fopKMOstksingle( t, x, m.value(i), s );
       kmostkops->set( 0, i, kmostack );
   }
   fopMerge   * mergeop   = new fopMerge( m );
   fopAdjoint * makepanel = new fopAdjoint( mergeop );

   num = 2;
   ops = new foperator*[num];
   ops[0] = kmostkops;
   ops[1] = makepanel;
}
```

The following Figures 6 and 7 show results of Kirchhoff modeling and migration using the chained operators.

VELOCITY ANALYSIS

[4] An important transformation in exploration geophysics takes the data as a function of shot-receiver offset and transforms it to data as a function of apparent velocity. Data is summed along hyperbolas of many velocities. This important industrial process is the adjoint to another that may be easier to grasp: data is synthesized by a superposition of many hyperbolas. The hyperbolas have various asymptotes (velocities) and various tops (apexes).

[4] Hector Urdaneta



Figure 6: Left frame = adjoint processing, right frame = adjoint processing + modeling. stacking-stackadjp [NR]



Figure 7: Left frame = inverse processing, right frame = inverse processing (10 iteration) + modeling. stacking-stackinvp [NR]

The construction of the velocity analysis operator, is done by chaining the NMO stack operator (see section) and the merge operator (see man pages **??**). The adjoint operator takes a set of linearly increasing slownesses values that are put into an axis. The adjoint operator applies first, for each slowness value, the NMO stack operator, which in turn, does the normal moveout and the stacking of the data. When this process is finished, we end up having one-dimensional data sets for each individual velocity. The merge operator finishes the job, putting all these one-dimensional spaces into a two-dimensional space where the new axis is a slowness axis.

A graph of inheritances for the velan operator is shown in Figure 8. Notice how you can also construct a velocity analysis operator, for the LMO operator (see next section), in the same way as for the NMO operator.

```
class fopVelan : public fopChain {
  public:
        //    time       offset    slowness
    fopVelan(Axis & t,  Axis & x,  Axis& s  );
};


fopVelan::fopVelan(Axis & t, Axis & x, Axis& s) {

int len = s.length;

// make a ( 1, len ) array of nmostack operators
fopArray * nmostkops = new fopArray(  1, len );

for( int i=0; i<len; i++ ){
    float slow = s.value(i);
    // build a single nmostack operator
    fopNMOstk * stkop = new fopNMOstk(t, x, slow );
    // put it in the array
    nmostkops->set( 0, i, stkop );
}

 // make a Merge operator
fopMerge * mergeop = new fopMerge( s );

 // make its adjoint
fopAdjoint * adjmerge = new fopAdjoint( mergeop );

// make a chain of the two
num=2;
ops = new foperator*[2];
ops[0] = nmostkops;
ops[1] = adjmerge;

}
```

The constructors for the `fopVelan` class are defined in the header file `fopvelan.h` (page 9). `fopvelan` (page 9) shows the coding of the `fopVelan` constructor.

An example of applying the `fopVelan` operator to field data is shown in Figure 9.

Figures 9 to 12 show examples of modeling, processing and inverse processing for the velocity analysis operator.

SLANT STACK AND PRECONDITIONED INVERSION